EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER

05022067

PUBLICATION DATE

29-01-93

APPLICATION DATE

15-07-91

APPLICATION NUMBER

03173790

APPLICANT: OKI ELECTRIC IND CO LTD;


INVENTOR: EBARA NAGANORI;

INT.CL.

: H03H 9/145

TITLE

SURFACE ACOUSTIC WAVE FILTER



ABSTRACT: PURPOSE: To improve humidity resistance without damaging the characteristic of the surface acoustic wave filter (SAW-F) by forming an SiO₂ film having specified thickness at the top of an interdigital electrode.

> CONSTITUTION: This SAW-F is equipped with Cr 1 to be an adhesive layer on the base, Al-Cu alloy 2 adding Cu to Al as an electrode layer, and SiO2, film 3 to cover the surface of the Al-Cu alloy 2 as a protecting layer to protect the Al-Cu alloy 2. Namely, the Al-Cu alloy 2 constituting the interdigital electrode is covered with the SiO₂ film 3 having thickness 100-1000, and a pattern is formed by lift-off. When the SiO₂ film 3 is thick, the characteristic is degraded since the surface acoustic wave vibration of the interdigital electrode is blocked and when the thickness is less than 1000, the level of a loss is not reduced so as to cancel the deviation of a frequency by making the film of the Al-Cu alloy 2 thin. When the SiO₂ film 3 is too thin, however, a humidity proof effect is lowered and therefore, the thickness more than 100 is required.

COPYRIGHT: (C)1993, JPO& Japio